

TITLE OF THE INVENTION
IMAGE PROCESSING SYSTEM CAPABLE OF APPLYING GOOD
TEXTURE SUCH AS BLUR

BACKGROUND OF THE INVENTION

5 The present invention relates to an image
processing system capable of applying a good texture
such as a blur and, more particularly, to an image
processing apparatus and method applicable to an
advanced-function digital camera serving as a virtual
10 camera, and a computer-readable program storage medium
used in the apparatus and method.

With the recent spread and functional advancement
of home or personal computers (PCs), personal digital
cameras have been developed to take the place of
15 conventional cameras using a silver halide film.
Also, higher-grade digital cameras having a CCD of
1,000,000 pixels or more are available.

This high-resolution digital camera is optimal for
entertainment purposes: an image can be displayed on a
20 high-resolution display of VGA or higher, or printed by
a large-size printer for A4 size or larger.

At the same time, an image processing technique,
which has conventionally been used in only special
study purposes, movie production, and printing jobs,
25 can be realized by a low-cost home computer along with
downsizing by computer techniques, reduction in power
consumption, and improvement of image processability.

09476910.010300

5 In the digital camera, as a high-resolution CCD of, e.g., 800,000 or 1,300,000 pixels is downsized from 1/2" to 1/4", the lens is also downsized to increase the F-number and shorten the focal length.

On the other hand, with the digital camera one can
15 only take a similar image regardless of who the
photographer is.

However, these problems can be solved by an image
25 processing technique.

For example, "Modeling of Blurring in Human Eyes and Binocular Stereoscopic Display by Modeling" (Kaneko

is
this
right?

10

15

2

20

25

5

10

20

25

characteristic is calculated using the set F-number, f-number, or focal pint position, and a new image is produced by image processing selectively using a low-pass filter and high-pass filter. However, the actual image is blurred, so no sharp image can be obtained from this image by a low-pass filter.

When the camera uses a zoom lens, it is difficult to always supply information about any one of the F-number, f-number, and focal pint position.

Such information depends on the system or camera in use, and cannot be generalized and hardly attains compatibility.

An image is blurred selectively using a low-pass filter and high-pass filter, so no good texture can be obtained.

In Jpn. Pat. Appln. KOKAI Publication No. 9-181966, an image sensed using a pair of image sensing lenses having a parallax is input, and distance information is calculated based on the information. The blur parameter is selected to apply the blur effect. This satisfies the above requirement. However, since this blur parameter includes any one of the F-number, f-number, and focal pint position, camera information is also necessary. The camera information is not compatible and general, and the blur does not give a good texture.

The present inventors have studied in pursuit of

09476910.010300

• The camera has high resolution with a sufficient
5 number of pixels, e.g., 800,000 pixels or more.

- The camera has information in the direction of depth of an object.

- Camera information except for an image and depth information is unnecessary.

15 in setting

 • The texture applied by image processing includes
a blur, color, and reflectivity.

20 • The blur, color, and reflectivity can be adjusted.
Unless these problems are solved, the texture of

To satisfy these conditions, realization of a digital camera capable of applying a texture is demanded.

The present invention has been made in

5

15

20

25

an in-focal pint position designation unit for

designating an in-focal pint position of the assumed
image sensing optical system;

5 a blur state calculation unit for calculating a
blur state from the distance information input by the
image input unit, the in-focal pint position designated
by the in-focal pint position designation unit, and the
parameter input by the parameter input unit; and

10 an image processing unit for applying the blur
effect to the image input by the image input unit in
correspondence with the blur state calculated by the
blur state calculation unit.

15 According to the second aspect of the present
invention, there is provided an image processing
apparatus for applying a blur effect to a captured
image, comprising:

an image input unit for capturing image
information including distance information to each
portion of an object to be photographed; and

20 an image processing unit for applying the blur
effect to the image input by the image input unit by
overwrite sequentially from an image portion having far
distance information.

25 According to the third aspect of the present
invention, there is provided an image processing
apparatus for applying a blur effect to a captured
image, comprising:

an image input unit for capturing image

09476910 010300

information;

an image processing unit having a first operation mode of applying the blur effect to only part of the image input by the image input unit, and a second operation mode of applying the blur effect to a remaining image portion;

a switching unit capable of externally switching an operation mode of the image processing unit from the first operation mode to the second operation mode; and

a display unit capable of displaying an image blurred by the image processing unit.

According to the fourth aspect of the present invention, there is provided an image processing method of assuming a characteristic of a virtual image sensing optical system, and applying a blur effect corresponding to a preset in-focus state to a captured image, comprising the steps of:

capturing image information including distance information to each portion of an object to be photographed;

inputting a parameter capable of deriving an effective aperture and focal length of the assumed image sensing optical system;

designating an in-focal pint position of the assumed image sensing optical system;

calculating a blur state from the input distance information, the designated in-focal pint position, and

09476910-010300

applying the blur effect to the input image in
correspondence with the calculated blur state.

capturing image information including distance information to each portion of an object to be photographed; and

According to the sixth aspect of the present invention, there is provided an article of manufacture comprising:

first computer-readable program means for providing a computer with a function of capturing image information including distance information to each portion of an object to be photographed;

first computer-readable program means for
25 providing a computer with a function of capturing image
information including distance information to each
portion of an object to be photographed;

second computer-readable program means for providing the computer with a function of inputting a parameter from which an effective aperture and focal length of the assumed image sensing optical system can be derived;

third computer-readable program means for providing the computer with a function of designating an in-focal pint position of the assumed image sensing optical system;

fourth computer-readable program means for providing the computer with a function of calculating a blur state from the input distance information, the designated in-focal pint position, and the input parameter; and

fifth computer-readable program means for providing the computer with a function of applying the blur effect to the input image in correspondence with the calculated blur state.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated

09476910-010300

in and constitute a part of the specification,
illustrate presently preferred embodiments of the
present invention, and together with the general
description given above and the detailed description of
5 the preferred embodiments given below, serve to explain
the principles of the invention.

FIG. 1 is a functional block diagram showing the
arrangement of the basic technique of the present
invention;

10 FIG. 2 is a view showing the imaging state of an
object before the focal point position of a lens;

FIG. 3A is a table showing numerical values
obtained by actually calculating equation (5);

15 FIG. 3B is a graph showing the calculation result
of equation (5);

FIG. 4A is a table showing numerical values
obtained by actually calculating equation (8);

FIG. 4B is a graph showing the calculation result
of equation (8);

20 FIG. 5 is a view showing the imaging relationship
of an object farther than the focal point position of
the lens;

FIG. 6 is a graph showing an actual blur appearing
as a combination of the states in FIGS. 3A, 3B, 4A,
25 and 4B;

FIG. 7A is a view for explaining a PSF charac-
teristic on a Z_{fo} plane nearer than Z_f ;

00476910-010300

FIG. 8 is a flow chart showing the sequence of actual processing according to the first embodiment of the present invention;

FIG. 10A is a view for explaining "occlusion" of
10 objects caused by the processing order as one of
problems which cannot be solved even by the first
embodiment of the present invention;

15 FIG. 10C is a view showing another solution to
"occlusion" in FIG. 10A;

20 FIG. 11B is a view showing a window for setting
aberration;

25 FIG. 12 is a view showing parameter setting (step S3) of a virtual camera and setting (step S4) of a focal pint position shown in FIG. 8;

FIG. 13 is a view showing a final image obtained by finally determined parameters;

FIG. 14 is a view showing the second embodiment;

FIG. 15 is a view showing the third embodiment;

5 FIG. 16A is a view showing a coma characteristic and expression method in order to explain the fourth embodiment;

10 FIG. 16B is a view showing another simpler example of the coma characteristic and expression method in order to explain the fourth embodiment;

FIG. 17A is a view showing the magnitude of a blur function determined by a radius d of a confusion circle 37 as an example of emphasizing blue in order to explain the fifth embodiment;

15 FIG. 17B is a view showing an example of emphasizing red in order to explain the fifth embodiment;

20 FIG. 18A is a view showing a red shift in order to explain a color dispersion characteristic of air and expression method according to the sixth embodiment;

FIG. 18B is a view showing a blue shift in order to explain the color dispersion characteristic of air and expression method according to the sixth embodiment;

25 FIG. 19A is a view showing an example of inputting not depth information in units of pixels but distance information in units of given objects in order to

00476910 010300

explain the seventh embodiment; and

FIG. 19B is a view showing a simpler example of applying one depth information to a given set of objects and applying the same information in units of objects in order to explain the seventh embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the presently preferred embodiments of the invention as illustrated in the accompanying drawings, in which like reference numerals designate like or corresponding parts.

Embodiments of the present invention will be described in detail below with reference to the several views of the accompanying drawing.

(First Embodiment)

The first embodiment of the present invention is shown in FIGS. 1 to 5.

The principle of the present invention will be explained by exemplifying the first embodiment.

FIG. 1 shows an arrangement as the functional block of a CPU 100 in order to explain the arrangement of the basic technique of the present invention.

This function may be implemented by either software or hardware.

In the software arrangement, respective functional blocks are stored in a computer-readable program storage medium 101 in units of subroutines or object

09476910.010300

An input/output processing unit 1 in FIG. 1 comprises, as an input unit, processing unit, and output unit for image data and parameters, a three-dimensional (3D) measurement data input unit 2, virtual camera setting unit 3, texture & lens setting unit 4, virtual focus setting unit 5, image memory 6, virtual camera parameter calculation unit 7, image calculation unit 8, image (recording) storage device 9, and the like.

The 3D measurement data input unit 2 means an image input unit 2 for unique physical property data having depth information in units of two-dimensional color tone data of an image. The virtual camera setting unit 3 means a parameter input unit 3, and the virtual focus setting unit 5 means an in-focal point position designation unit 5.

The input/output processing unit 1 has a means and function of receiving setting values from the parameter input unit 3, texture & lens setting unit 4, and in-focal pint position designation unit 5 on the basis of physical property data from the image input unit 2.

The image input unit 2 may be implemented by mounting an actual measurement camera, or by analog video information, compressed data, or proper interface means.

The parameter input unit 3, texture & lens setting

unit 4, and in-focal pint position designation unit 5 may be a keyboard or mouse, and preferably have a user-friendly structure using image icons.

5 The image memory 6 temporarily stores input image data from the image input unit 2.

Although not shown, an interface circuit may be arranged on the input stage of the image memory 6 to decompress compressed image data, convert data, and the like.

10 The virtual camera parameter calculation unit 7 converts virtual camera parameters from the parameter input unit 3, texture & lens setting unit 4, in-focal pint position designation unit 5, and the like.

Position ↑
15 The image calculation unit 8 comprises a confusion circle calculation means, blur state calculation means, and image processing means. The image calculation unit 8 executes predetermined calculation such as confusion circle calculation, blur state calculation, and image processing (to be described later) using input data
20 from the image memory 6 and a virtual camera parameter from the virtual camera parameter calculation unit 7.

A method and algorithm for realizing the means and functions of the virtual camera parameter calculation unit 7 and image calculation unit 8 are the most
25 important in the present invention.

Note that the image memory 6 may be omitted. The image (recording) storage device 9 stores the

09476910.010300

calculation results of the image calculation unit 8.

A definitely different appendix of this arrangement from the prior art will be explained.

Jpn. Pat. Appln. KOKAI Publication No. 7-21365
5 discloses "a method of inputting, from a camera, image data, depth data, and camera information such as the F-number and focal length, separately setting a virtual image sensing parameter, calculating a blur parameter from the input values, comparing a calculated blur
10 parameter with actual blur corresponding to the set value with the camera information such as the F-number and focal length, selectively using a low-pass filter and high-pass filter, and outputting a new image to an image memory upon image processing".

15 That is, current camera conditions and virtual camera conditions to which an image including a blur state is input are compared with each other to newly produce an image.

Jpn. Pat. Appln. KOKAI Publication No. 9-181966
20 discloses "a method of inputting an image sensed using a pair of image sensing lenses having a parallax, calculating distance information based on the information, and selecting a blur parameter including any one of the F-number, f-number, and focal pint
25 position, thereby applying a blur effect".

In this method, new photographing conditions are applied to current photographing conditions including

09476910 "010300

camera setting conditions, and image processing is performed to apply a blur.

Compared to these prior arts, the present invention realizes the following arrangements and effects.

• Video information is only image data including an image that is photographed by a three-dimensional measurement camera.

• The system of the present invention adjusts virtual camera settings such as the F-number, focal length, stop value, and the like.

• The performance of a lens which characterizes a blur state, the color dispersion characteristic of the lens, the dispersion characteristic of air at that time, the blur state function based on distance, and the like can be appropriately set.

• The user can enjoy a virtual camera while focusing on a target object.

The basic concept of the present invention will be explained with reference to FIGS. 2 to 6B.

According to this concept, the blur radius (confusion circle) when the focus is adjusted to a given position is estimated as a rough value to obtain characteristics in this conditions.

FIG. 2 shows the imaging state of an object in front of the focal pint position of the lens.

Let f be the focal length of the lens, Zf be the

09476910-010300

position of an object to which the focus is adjusted,
zfo be the focal pint position, Z be the distance to an
observation place, Zo be the distance on the imaging
side to the observation place, and D be the effective
5 aperture of the lens. The origin is the center of the
lens.

When a combination of lenses are used, they are
assumed to be a single lens.

Letting the imaging plane be on the positive side
10 of the lens, and d be the blur radius at the visual
point Zf when the focus is adjusted to Z, the blur
radius d is calculated using geometrical relations:

$$d/(Z_o - Z_{fo}) = D/Z_o \quad \dots (1)$$

$$(1/Z) + (1/f) = 1/Z_o \quad \dots (2)$$

$$15 \quad (1/Z_f) + (1/f) = 1/Z_{fo} \quad \dots (3)$$

thereby obtaining

$$d = D\{(1/Z_f) - (1/Z)\}/\{(1/Z_f) + (1/f)\} \quad \dots (4)$$

for $Z_f < 0$ and $Z < 0$.

For descriptive convenience, the absolute values
20 of Z_f and Z are used to obtain

$$d = D\{(1/|Z|) - (1/|Z_f|)\}/\{(1/f) + (1/|Z_f|)\} \quad \dots (5)$$

FIG. 3A shows numerical values obtained by actual
calculation.

25 In FIG. 3A, d/D calculated at three focal pint
positions $Z_f = 0.3$ m, 1 m, and 10 m of a lens having
 $f = 50$ mm are listed in the table.

09476910"010300

FIG. 3B is a graph showing the calculation results.

In FIG. 3B, as the lens comes near to 20 cm or less, the confusion circle becomes larger. When the focus is set to a sufficiently far distance, d/D asymptotically decreases.

A position farther from the focus is considered.

In this case, an imaging relationship as shown in FIG. 5 is obtained.

A simple geometrical equation:

$$d/(Zf - Z_0) = D/Z_0 \quad \dots (6)$$

yields

$$d = D\{(1/Z) - (1/Zf)\}/\{(1/Zf) + (1/f)\} \quad \dots (7)$$

for $Zf < 0$ and $Z < 0$

For descriptive convenience, the absolute values of Zf and Z are used to obtain

$$d = D\{(1/|Zf|) - (1/|Z|)\}/\{(1/f) + (1/|Zf|)\} \quad \dots (8)$$

FIG. 4A shows numerical values obtained by actual calculation.

In FIG. 4A, d/D calculated at three focal point positions $Zf = 0.3$ m, 0.6 m, and 2 m of a lens having $f = 50$ mm are listed in the table.

FIG. 4B is a graph showing the calculation results.

For $Zf = 0.3$ m, as the lens moves away slightly, blur abruptly increases. When the focus is adjusted to a far distance of 2 m, blur does not increase.

For example, for $Zf = 0.3$ m, the radius d of the

00476910-010300

For $z_f = 0.6$ m, \underline{d} reaches only 5% of D at a double distance of 1.2 m, and asymptotically increases to 10%.

FIG. 6 shows this state.

The value \underline{d} can be calculated by this quantitative analytic function.

More specifically, the size of the confusion circle \underline{d} can be determined by the F-number and distance for adjusting a set focus using the focal length \underline{f} of the lens, the effective aperture $2D$, or equation (9):

These parameters do not include any camera information in the direction of depth of an image.

KOKAI Publication No. 7-21365.

That is, in the camera in Jpn. Pat. Appln. KOKAI

Publication No. 7-21365, an image and depth information are received, and camera conditions are set only within an image processing apparatus.

5 The present invention considers the size of the confusion circle d of blur. To actually express a natural blur or perspective, it is important to determine the shape of PSF (Point Spread Function) representing a blur.

10 FIG. 6 shows a blur characteristic PSF_n on a side near the lens and a blur characteristic PSF_f on a far side, which are empirically obtained for a general lens.

FIGS. 7A and 7B are views for explaining the PSF characteristic.

15 FIG. 7A is a view for explaining PSF on the Z_{fo} plane nearer than Z_f. In general, the light quantity tends to be larger at the periphery.

FIG. 7B is a view for explaining PSF formed by an image farther than Z_f. In general, this PSF shape greatly changes depending on the lens.

20 In FIGS. 7A and 7B, only astigmatism is considered. In practice, coma and chromatic aberration are present to complicate PSF.

25 However, presumably astigmatism free from any coma and chromatic aberration can most sensitively and naturally express a blur.

Astigmatism is radially symmetrical. Letting the convex function as shown in FIG. 7B be of A type, and

09476910.010300

for A type,

5 for B type,

The function is normalized by G so a value outside the range $-d \leq r \leq d$ is 0 and the spatial volume is 1.

10

In step (S1), image data is input.

15

In step (S2), lens characteristics are set.

20

In step (S3), camera parameters are set.

25

In step (S4), focus information in photographing is set.

In step (S5), the blur function is calculated as follows from distance information of the image on the basis of the set values in step (S2) to step (S4), and a blur state corresponding to the distance is applied to the image data.

- 20 In step (S7), it is determined if the image
displayed on the window is OK. If OK in step (S7), the
image is stored in the image storage device 9; if NG,
the flow returns from step (S1) to step (S4).

By the above sequence and arrangement, the present invention can realize an image processing apparatus which can contribute to implementation of a digital camera system capable of solving the conventional

This sequence is merely an example, and the order may be changed.

5

10

15

20

25

In this case, \underline{f} and D are calculated from lens

information and the F-number using equation (9), respectively.

In step (S15), calculation starts for each pixel (i).

5 The start cell is selected, and d is calculated from D , Z_f , and f in step (S14) and the Z value of each pixel.

In this case, two d values are calculated from the relationship of Z and Z_f , and prepared as d_1 and d_2 .

10 More specifically, when the absolute value of Z is smaller than Z_f , d_1 is used. When the absolute value of Z is larger than Z_f , d_2 is used.

In step (S16), a blur function obtained by lens characteristics is prepared.

15 The A type convex function uses g_a obtained using a_1 to a_3 and the like, whereas the B type concave function uses g_b obtained using b_1 to b_3 and the like.

When a function independent of distance is used, the blur function is calculated in step (S13).

20 When the function depends on the difference between Z and Z_f , the blur function is calculated every time.

In step (S17), the blur state at a point j by R_i is calculated.

25 In this case, g is switched between g_a and g_b similar to step (S16) depending on whether the blur state is given by the A type convex function or B type

00476910.010300

concave function.

In general, when the point j is nearer the lens than $2f$, the A type convex function is used. When the point j is farther, the B type concave function is used.

5 Since g is normalized, the sum of R_i and a value determined by the distance between the coordinates of i and j is the value j .

Only calculation for R has been described, but this also applies to G and B .

10 This sequence returns to step (S15) and is executed for all the pixels.

In step (S18), the blur state at the given point j influences the whole range of the blur function for the point i , and thus is given by the sum of R_{ji} for i .

15 In step (S19), the flow ends.

This method can provide an image to which a natural, strong blur or the like is applied.

Strictly speaking, however, several problems remain unsolved.

20 FIG. 10A shows one of the problems, i.e., "occlusion" between objects caused by the processing order.

In FIG. 10A, the lens is focused on a near person image 16, and blur is applied to a far tree image 11. The blur of the tree image 11 occludes the person image 16.

25

This is "occlusion" caused since processing is

00476910-010300

FIG. 10B shows a solution to "occlusion".

In this case, processing starts from a deeper object image 12. Then, a person image 10 is overwritten on the object image 12 to give clear depth information between the respective objects.

For example, some of the following processes are required.

• When the near object 10 is not in focus, the periphery representing the blur state of the object is partially made transparent, as needed. Then, a new near object color is add to color information farther than the pixel.

25 As shown in FIG. 10C, since an image has depth information in units of pixels, processing starts from a pixel having a large absolute value of Z.

In this example, processing starts from the farthest pixel of the mountain image 12. Then, the tree image 11 and person image 10 are sequentially processed.

5 Also in this case, some of the following processes are required.

· When the near object 10 is in focus, color information farther than the pixel is discarded and replaced with a new near object color.

10 · When the near object 10 is not in focus, the periphery representing the blur state of the object is partially made transparent, as needed. Then, a new near object color is add to color information farther than the pixel.

15 FIGS. 11A to 13 are views for explaining detailed processing in the first embodiment.

FIGS. 11A to 13 show images on the display of an actual computer, but may be the liquid crystal display of a camera.

20 FIGS. 11A to 11C show windows for setting lens characteristics.

By setting a default value in advance, the user need not set lens information.

25 In this example, three characteristics, i.e., the lens, aberration, and blur function are set.

FIG. 11A shows a window 13 for setting the lens.

In this case, whether the lens has a single focus

00476910-010300

16 or zoom 17 is selected.

When the single-focus lens is selected, an f-number 18 is input. When the zoom is selected, maximum and minimum f-numbers are input. The f-number
5 may be numerically input or may be selected for data presented to the user.

Then, a lens aperture 19 is similarly input.

FIG. 11B shows a window for setting aberration.

By clicking an aberration tag 20, the window is
10 switched to the aberration setting window.

This window is used to select any one of astigmatism 21, coma 22, and chromatic aberration 23. For coma and chromatic aberration, the type of
aberration can be selected.

15 For coma, the degree of shift from the center can be selected. For chromatic aberration, the components of red, blue, and the like, and the aberration strength can be selected.

20 This strength may be set using a volume or the like. If a special effect button 24 is used, a filter effect may be obtained.

For example, in a single-lens reflex camera, when the stop is stopped down, the polygon (hexagon) of the stop functions as a filter, and strong reflection or
25 the like appears on a window with this polygonal shape.

The aberration can assume this effect or an effect as if the user freely used a filter.

09476910.010300

By setting the respective aberrations, a plurality of effects can be simultaneously obtained.

For example, if astigmatism and coma are selected, their effects can be simultaneously exhibited.

5 In FIG. 11B, coma is selected from several set patterns. Alternatively, the user may set coma parameters by himself.

FIG. 11C shows a function of setting the shape of a point spread function within a confusion circle.

10 FIG. 11C shows only settings of the most important astigmatism, but the same method is adopted for the coma and chromatic aberrations.

In FIG. 11C, a near function 26 represents a blur state nearer than the in-focal point position, and a far function 27 represents a farther blur state.

15 As the initial setting value, the near function takes a value smaller at the center than the periphery as a concave function, and the far function takes a value larger at the center than the periphery as a convex function. This is a lens characteristic and can be freely changed.

20 The function can be freely set by the user except that the radius of a confusion circle determined by a computer is rotation-symmetrical owing to the astigmatism.

25 To set the function, although the user may input a figure, he/she can designate a value in the direction

09476910-010300

of radius (r) with a mouse, and drag the function to freely change the function.

Note that the function is normalized so that its integral is constant.

5 The actually calculated function may be different
from the function on the window.

To present an easy-to-recognize function, $G(r)$, $G(r)/r$, or $G(r)/r^2$ may be adopted.

FIG. 12 shows parameter setting (step S3) of the
virtual camera and setting (step S4) of the focal pint
position shown in FIG. 8.

For a simple arrangement and user's convenience, these settings can be done on a single display.

15 In this example, the user can set an F-number 28
and focal pint position 29 by adjusting volumes (28
and 29).

For example, if the user wants to emphasize a blur, he/she decreases the F-number to 1.4.

By setting this value, D is calculated by equation
 20 (9) using a predetermined f-number, and applied to
 equations (5) and (8).

The image shown in FIG. 12 is a window for a monitor (not shown).

25 If all the pixels are used for the monitor window,
an enormous amount of calculation must be executed,
which takes a long time until results are obtained.
Hence, only some of all the pixels are used.

5 Of the four quadrants, e.g., the second and fourth quadrants display images before processing, and the first and third quadrants display images after processing.

The user can freely determine the F-number and focus for the virtual camera regardless of an actual camera.

FIG. 13 shows a final image obtained by finally
20 determined parameters.

25 This blur can be freely changed by changing the blur function shape of astigmatism. The blur is natural because its amount is based on the lens theory. The degree of blur depends on the lens properties.

By adding coma, the background image fades off,
5 resulting in a natural image like the one sensed by the
human eye. This influence can also be freely set.

10 Chromatic aberration is a phenomenon in which a blurred portion shifts to red or blue. This phenomenon is also natural for the visual sense, and can attain many effects.

15 FIG. 14 shows the second embodiment.

FIG. 14 shows the embodiment for the example of
20 FIG. 12 in which the user interface is enhanced.

In this embodiment, the F-number is set with a volume, and the focus is adjusted to the head of a

person image 31.

Depth information of the head position is calculated to obtain Z, and a volume position 29 at the lower portion in FIG. 14 automatically moves to determine the focal pint position.

Since distance information in units of pixels includes errors, distances near a designated point may be averaged. The radius or number of pixels subjected to averaging may be separately set.

Upon completion of the setting, an "OK" button (not shown) is clicked to start calculation of all the pixels. The results are displayed, and if necessary, printed or stored in a storage device 9.

(Third Embodiment)

FIG. 15 shows the third embodiment.

The basic concept and arrangement method of the third embodiment are the same as in the first embodiment.

FIG. 15 shows the embodiment in which the user interface is enhanced with a zoom function.

In the first embodiment, a zoom 32 determines the focal length of the lens. In FIG. 15, the zoom 32 can be set at the upper portion of the window.

The displayed maximum and minimum focal lengths are set by lens settings.

By changing the zoom ratio, an image may be enlarged and displayed at the center. Instead, to

00476930 010300

The focal pint position is determined using the
5 distance to a designated pixel of the object (or the
average of several pixels).

If an F-number 28, the zoom 32, and the focal pint position 29 are determined, expressing including a blur state is determined, and thus an image can be processed.

In FIG. 15, reference numeral 33 denotes an enlargement button; and 34, a whole button. By clicking the enlargement button 33, the whole outer frame 40 appears on the window to represent a zoom state.

25 Upon completion of the setting, an "OK" button
(not shown) is clicked to start calculation of all the
pixels. The results are displayed, and if necessary,

printed or stored in a storage device 9.

(Fourth Embodiment)

FIGS. 16A and 16B show the fourth embodiment.

The basic concept and arrangement method of the
5 fourth embodiment are the same as in the first
embodiment. In the fourth embodiment, a coma
characteristic is set in setting lens characteristics.

FIG. 16A shows a coma characteristic and
expression method. Reference numeral 35 denotes a coma
10 characteristic.

Coma represents radial distortion of an image when
the image shifts from the center of the lens. FIG. 16A
shows aberration at a distance \underline{r} from the center.

This aberration radially extends outward from the
15 center. In the fourth embodiment, the aberration is
represented by a parabola using the central position
(pixel of interest) as a focus in order to express
aberration extending radially from the center, like the
coma characteristic 35.

A line is drawn from the pixel to the center of
20 the window. Letting \underline{r} be the normal direction, and rv
be the vertical direction, the parabola is given by a
quadratic curve with respect to rv . The parabola is
approximated by a function which ends the parabola at a
25 distance \underline{d} in the direction rv .

Another example is more simply a confusion circle
36 having a radius \underline{d} . A method of deriving a blur

09475910-010300

function as astigmatism is the same as in FIG. 16A. Alternatively, the center of the confusion circle 36 may be shifted by r_0 from a pixel of interest, as shown in FIG. 16B.

5 In this case, r_0 may be set as a default value or by a user.

 The value r_0 is a function of \underline{r} , and basically a linear function of \underline{r} . The value r_0 becomes larger as it moves outward.

10 Coma fades toward the periphery of the window.

 In general, the lens is designated to reduce coma. However, coma is close to the human visual sense. By virtually adding coma, like the fourth embodiment, a very-high-quality image can be expressed.

15 Furthermore, very natural image expression close to the human visual sense can be attained by not simply blurring the image periphery, but combining depth, blur, and another aberration in consideration of depth information, like the fourth embodiment.

20 In the fourth embodiment, the variable \underline{r} of PSF changes within the range of the size \underline{d} of the confusion circle.

 However, the variable \underline{r} need not always change within the range of \underline{d} . In short, the possible range of the variable \underline{r} of PSF need only increase for a large confusion circle, and decrease for a small confusion circle.

25

00476910-010300

(Fifth Embodiment)

FIGS. 17A and 17B show the fifth embodiment.

The basic concept and arrangement method of the fifth embodiment are the same as in the first embodiment. In the fifth embodiment, a chromatic aberration characteristic is set in setting lens characteristics.

FIGS. 17A and 17B show a chromatic aberration characteristic and expression method. FIG. 17A exemplifies the size of a blur function determined by a radius d of a confusion circle 37.

In FIG. 17A, reference numeral 38 denotes an inner circle.

The inner color of the inner circle 38 is that of a central pixel. In an outer range $d-\Delta$, blue is emphasized in the example of FIG. 17A, and red is emphasized in the example of FIG. 17B.

This chromatic aberration provides an image reddish or bluish at the window periphery.

In general, the lens is designed to reduce chromatic aberration. However, chromatic aberration is close to the human visual sense. Thus, chromatic aberration virtually added in the fifth embodiment can express a very-high-quality image.

Moreover, very natural image expression close to the human visual sense can be attained by not simply blurring the image periphery, but combining depth, blur,

(Sixth Embodiment)

5 The basic concept and arrangement method of the sixth embodiment are the same as in the first embodiment. In setting lens characteristics, a color dispersion characteristic in air is set.

The state of air greatly changes depending on the time and place. For example, on a mountain on a fine day, the amount of ultraviolet rays is large, and a far place looks bluish.

Near the skyline or horizon, red components are emphasized by a dust dispersion characteristic in air, resulting in a sunset or sunrise image.

25 In this example, when the distance has a certain
depth or more, the red range is emphasized.

In this case, a threshold z_{th} of Z is set.

Alternatively, the red shift amount may be increased stepwise in accordance with the level of Z.

FIG. 18B shows a blue shift.

5 In this example, when the distance has a certain depth or more, the blue range is emphasized.

In this case, the threshold Z_{th} of Z is set. Alternatively, the blue shift amount may be increased stepwise in accordance with the level of Z.

10 Accordingly, the sixth embodiment can apply natural perspective later.

In general, a landscape is often photographed using a polarizing filter which adds higher contrast and better color than actual ones to far image portions. In practice, the quality of a far image is low.

15 In the sixth embodiment, an image can be easily improved by simulating a clear day, cloudy day, evening, and the like.

Capturing information in the direction of depth realizes natural expression. The user can enjoy photographing in combination with a blur or the like. (Seventh Embodiment)

FIGS. 19A and 19B show the seventh embodiment.

20 The basic concept and arrangement method of the seventh embodiment are the same as in the first embodiment. The seventh embodiment will exemplify another data input means.

In the first embodiment, input data has depth

09476910 030300

5

10

15

20

25

FIG. 19A shows an example of the seventh embodiment.

5 In this case, the image is divided into a person
image 10, tree image 11, and mountain image 12, and
each image is provided with depth information. To
measure depth information by the active method, a near
object, farther object, and background may be
10 separately photographed to input distance information
in units of objects. Alternatively, the measurement
method may change depending on the object to be
processed.

20 FIG. 19B shows a simpler example.

In this example, each of the person image 10, tree image 11, object image 12, and a sky image 39 has the same information such as Z1, Z2, Z3, or Z4 as a plate-like image.

This process is used when the depth is measured by

a very simple measurement device or at a plurality of points on a measurement display.

Even when an object is segmented by cutting out a two-dimensional image in accordance with the gradation, color, or user' intention, software for executing this embodiment can be applied by adding depth information later.

In this case, cut-out of the window and setting of the depth in units of objects may be contained in software for executing this embodiment.

The present invention exemplified by the above-described embodiments include the following appendixes (1) to (23) in addition to the first to seventh embodiments.

Appendix (1): An image processing apparatus for assuming the characteristic of a virtual image sensing optical system, and applying a blur effect corresponding to an in-focus state to a captured image, is characterized by comprising

an image input means for capturing image information including distance information to each portion of an object to be photographed,

a parameter input means for inputting a parameter from which the effective aperture and focal length of the assumed image sensing optical system can be derived,

an in-focal pint position designation means for designating the in-focal pint position of the assumed

09476910-010300

a confusion circle calculation means for calculating a confusion circle from the distance information input by the image input means, the in-focal pint position designated by the in-focal pint position designation means, and the parameter input by the parameter input means,

an image processing means for applying the blur effect to the image input by the image input means in correspondence with the blur state calculated by the blur state calculation means.

the step of capturing image information including distance information to each portion of an object to be photographed,

25 the step of inputting a parameter from which the effective aperture and focal length of the assumed image sensing optical system can be derived,

the step of designating the in-focal pint position
of the assumed image sensing optical system,

the step of calculating a confusion circle from
the input distance information, the designated in-focal
5 pint position, and the input parameter,

the blur step of calculating a blur state using a
point spread function (PSF) within a range
corresponding to the size of the calculated confusion
circle, and

10 the step of applying the blur effect to the input
image in correspondence with the calculated blur state.

Appendix (3): A storage medium for a computer-
readable program stored to assume the characteristic of
a virtual image sensing optical system and apply an
15 effect equivalent to blur corresponding to an in-focus
state to a captured image in an image processing
apparatus, is characterized by comprising

a first computer-readable program means for
providing a computer with a function of capturing image
20 information including distance information to each
portion of an object to be photographed,

a second computer-readable program means for
providing the computer with a function of inputting a
parameter from which the effective aperture and focal
25 length of the assumed image sensing optical system can
be derived,

a third computer-readable program means for

00476910-010300

providing the computer with a function of designating an in-focal pint position of the assumed image sensing optical system,

5 a fourth computer-readable program means for providing the computer with a function of calculating a confusion circle from the input distance information, the designated in-focal pint position, and the input parameter,

10 a fifth computer-readable program means for providing the computer with a function of calculating a blur state using a point spread function (PSF) within a range corresponding to the size of the calculated confusion circle, and

15 a sixth computer-readable program means for providing the computer with a function of applying the blur effect to the input image in correspondence with the calculated blur state.

20 Appendix (4): A storage medium for a computer-readable program stored to apply a blur effect to a captured image in an image processing apparatus, is characterized by comprising

25 a first computer-readable program means for providing a computer with a function of capturing image information including distance information to each portion of an object to be photographed, and

a second computer-readable program means for providing the computer with a function of applying the

09476910 010300

blur effect to the input image by overwrite sequentially from an image portion having far distance information.

Appendix (5): An image processing apparatus is characterized by comprising

5 a means for inputting image data including depth information,

a means for setting a parameter for expressing a lens characteristic,

10 a means for setting any one of a focal length, F-number, field angle, and effective aperture,

a means for setting a distance for adjusting the focus,

a means for calculating expression of an image texture including a blur from the virtual camera

15 setting values and the depth information of the image, and

a means for storing a calculation result in a memory.

20 Appendix (6): An image processing apparatus according to appendix (5) is characterized by further comprising means for inputting an image having depth information in units of pixels of a two-dimensional image.

25 (Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the first embodiment.

00476930.010300

(Function and Advantage)

Only image data including photographed depth information is input, and a virtual camera can be constituted by only set lens information and a position to get into focus.

This virtual camera can express a natural stereoscopic impression and blur, and the texture state by changing photographing conditions and setting lens characteristics.

Appendix (7): An image processing apparatus according to appendix (5) is characterized in that the blur function is a point spread function (PSF) calculated in units of pixels from the focal length of a lens, the F-number or aperture, the object distance, and the depth information of the image.

Appendix (8): An image processing apparatus according to appendix (5) is characterized in that the blur function has a variable function shape, and is a concave function or convex function determined by a focal pint position and an object distance to be calculated.

(Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the first embodiment.

(Function and Advantage)

Only image data including photographed depth information is input, and a virtual camera can be

09476910-010300

This virtual camera can express a natural stereoscopic impression and blur, and attain an ideal texture and artificial texture by changing
5 photographing conditions and setting lens characteristics.

The corresponding mode is described in the first embodiment.

Only image data including photographed depth
20 information is input, and a virtual camera can be
constituted by only set lens information and a position
to get into focus.

Appendix (10): An image processing apparatus according to appendix (5) or (9) is characterized in

that a user designates a position on a window to determine a focal pint position using depth information of the window.

Appendix (11): An image processing apparatus according to appendix (5) or (11) is characterized in that a user freely changes the F-number with a volume while designating a focal pint position on a designated window, and a calculation result using a thumbnail image obtained by thinning out an input image is displayed to interactively obtain parameter setting capable of confirming designation of the focal pint position and F-number.

Appendix (12): An image processing apparatus according to appendix (5) is characterized in that a user can change a zoom ratio by changing an f-number.

Appendix (13): An image processing apparatus according to appendix (5) is characterized in that the central point of a zoom and a position to get into focus are set in setting a zoom ratio, and the central coordinates of the zoom and the depth information of the point are used to calculate enlargement on a window and a blur state or to interactively determine a parameter.

(Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the second embodiment.

00476910-010300

(Function and Advantage)

Only image data including photographed depth information is input, and a virtual camera can be constituted by only set lens information and a position to get into focus.

By this virtual camera, only a position to get into focus can be set to focus on that position. Another stereoscopic impression and texture can be interactively set while an intermediate result is confirmed.

Appendix (14): An image processing apparatus according to appendix (13) is characterized in that an outer frame in an area to be enlarged and displayed without changing a display ratio is displayed in setting the zoom ratio.

Appendix (15): An image processing apparatus according to appendix (5) is characterized in that a window is enlarged based on the central coordinates of a zoom designated by a user, a focal pint position on the window is designated to determine the focal pint position, the F-number is freely changed with a volume, and a calculation result using a thumbnail image obtained by thinning out an input image is displayed to interactively obtain parameter setting capable of confirming designation of the central position of the field angle, the zoom ratio, and the F-number.

(Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the third embodiment.

(Function and Advantage)

5 Only image data including photographed depth information is input, and a virtual camera can be constituted by only set lens information and a position to get into focus.

10 By this virtual camera, only a position to get into focus and a zoom ratio can be set to focus on that position and zoom. Another stereoscopic impression and texture can be interactively set while an intermediate result is confirmed.

15 Appendix (16): An image processing apparatus according to appendix (15) is characterized in that the blur state is expressed using the influence of coma which changes depending on the distance and azimuth from the center of an image.

20 Appendix (17): An image processing apparatus according to appendix (5) or (16) is characterized in that an asymmetrical point spread function is calculated for coma using a blur function obtained by shifting the central position of the radius of a confusion circle in accordance with the distance from
25 the central position of an image.

(Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the fourth

09476910.010300

embodiment.

(Function and Advantage)

Only image data including photographed depth
information is input, and a virtual camera can be
5 constituted by only set lens information and a position
to get into focus.

This virtual camera can adopt the influence of the
coma, and can achieve an image texture like the one
obtained by the human visual sense.

10 Appendix (18): An image processing apparatus
according to appendix (5) is characterized in that the
influence of chromatic aberration is adopted.

Appendix (19): An image processing apparatus
according to appendix (5) or (18) is characterized in
15 that a range $d-\Delta$ from \underline{d} on a point spread function for
the radius (d) of a symmetrical confusion circle is set
as a chromatic aberration influence range, and red
aberration or blue aberration is applied.

(Corresponding Mode of Carrying Out the Invention)

20 The corresponding mode is described in the fifth
embodiment.

(Function and Advantage)

Only image data including photographed depth
information is input, and a virtual camera can be
25 constituted by only set lens information and a position
to get into focus.

This virtual camera can adopt the influence of

09476910.010300

chromatic aberration, and can achieve an image texture like a bluish one obtained by the human visual sense.

Appendix (20): An image processing apparatus according to appendix (5) is characterized in that the influence of a color shift in air is used.

Appendix (21): An image processing apparatus according to appendix (5) or (20) is characterized in that the blue range or red range of a color characteristic at a given distance or more is emphasized or decreased.

(Corresponding Mode of Carrying Out the Invention)

The corresponding mode is described in the sixth embodiment.

(Function and Advantage)

Only image data including photographed depth information is input, and a virtual camera can be constituted by only set lens information and a position to get into focus.

This virtual camera can adopt the influence of color dispersion in air, and can achieve an image texture like the one obtained by a natural sense such that the vicinity of the horizon becomes reddish.

Appendix (22): An image processing apparatus according to appendix (5) is characterized by further comprising a means for inputting, as a set of units, depth information and image information in units of pixels or areas for each object.

09476910.010300

5 (Corresponding Mode of Carrying Out the Invention)

(Function and Advantage)

Processing according to the present invention is done for an input to the virtual camera including an image formed by processing a general two-dimensional image, an easily obtained three-dimensional measurement image, an image obtained by a 3D authoring tool, and an animation image.

Even an image focused on the entire window, like
25 an image photographed by a compact camera, can be
processed into an image having a blur, like an image
photographed by an expensive single-lens reflex camera.

According to the modes described in the first and fourth embodiments, the blur is natural because a virtual optical system is assumed.

5 According to the modes described in the first and fourth embodiments, it is possible to freely designate an in-focal point position, and thus freely blur a far view or near view.

10 According to the modes described in the first and fourth embodiments, the blur can be reproduced in an arbitrary virtual optical system.

According to the modes described in the second to fifth embodiments, "occlusion" generated in applying a blur can be removed.

15 According to the mode described in the third embodiment, the blur can be applied to the entire window after the blur effect is confirmed at part of the window. This increases the processing efficiency.

20 As has been described above, the present invention can provide an image processing system capable of contributing to implementation of a digital camera system capable of solving the conventional problems and practically improving the texture of a digital camera serving as a virtual camera, thereby effectively applying a texture such as a blur.

25 Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to

09476910.010300

the specific details and representative embodiments
shown and described herein. Accordingly, various
modifications may be made without departing from the
spirit or scope of the general inventive concept as
5 defined by the appended claims and their equivalents.

09476910 010300